Smart for Greenlife !

Advantages

- 8-tenant energy monitoring and billing for 3 phase configuration, 24-tenant energy monitoring and billing for 1 phase 2 wire configuration
- Three times smaller than competitor's MMU8 in size
- Can be easily connected to PC, Cell Phone and iPad for remote Monitoring

Dimensions

15.75"

Front

7.87"   Side

5.12"

Top   5.12"

5.12"

Unit : inches

Dedicated Current Sensors (CTs)

5A Solid-Core   **5A Split-Core**

For use with regular 5A output CTs (3-phase)

50A Solid-Core   **100A/200A Solid-Core**   **50/100/200/400/600A Split-Core**

Features

- 4.3" LCD display with Ethernet
- Displays the kWh and kW for up to eight tenants
- Revenue-grade accuracy
- Supports both split-core and solid-core CTs
- Parallel connect three CTs to the same terminal to get a merged reading
- Meter can be used in the following configurations:

1-Phase, 2-Wire	3-Phase, 3-Wire
1-Phase, 3-Wire	3-Phase, 4-Wire
2-Phase, 3-Wire	

- Non-volatile memory for permanent storage of kWh and configuration data

Ordering Code

Ordering Code	Description
SMMU-8-A	8-tenant mutiple meter unit with 4.3" LCD display Compatible with 5 Amp CT
SMMU-8-B	8-tenant mutiple meter unit with 4.3" LCD display Compatible with 50/100/200/400/600 Amp CT
SMB350C-8-A	Multiple meter with kW & kWh (w/o 4.3" LCD and case) Compatible with 5 Amp CT
SMB350C-8-B	Multiple meter with kW & kWh (w/o 4.3" LCD and case) Compatible with 50/100/200/400/600 Amp CT
ACS35C-E	Meter reading touch panel with Ethernet
DR-15-24	15W, 24VDC power supply, input 100~240Vac

Note: Dedicated CT ordered separately

SMB350C

ACS35C

SMMU-8